PLANETARY GRINDER TOOLING AND ACCESSORIES

PCDS AND CARBIDES

| Part # | Description | Best Uses |
|--------|--------------------------|--|
| 9555 | 2-UP PCD- MICRO | Remove heavy stock, adhesive, thin set, and epoxies |
| 9557 | 4-UP PCD- MICRO | |
| 9554 | 1-UP PCD- 1/2 ROUND | |
| 9556 | 2-UP PCD- 1/2 ROUND | |
| 7268-2 | CARBIDES | Remove coatings, glue, thin set, and thin mastics |
| 9521 | CARBIDE & TOOLING HOLDER | Use to attach the above tooling to National Grinders |
| 9550 | SCREW | Use to attach tooling to the above holder |
| 9500 | BLANKS | |











9557 7268-2

METAL BOND DIAMONDS

Perfect for leveling concrete high spots and repairing imperfections as well as creating the perfect profile for accepting new coatings and epoxies, or preparing concrete for polishing.

| Part # | Description | Best Uses | | |
|--|-------------|--|--|--|
| FULL BAR DIAMOND INSERTS | | | | |
| 9508-16 | 16 GRIT | Remove epoxy as well as heavy and light sealers | | |
| 9508-16SB | 16 GRIT | Remove various coatings, and profiles on HARD concrete only | | |
| 9508-30 | 30 GRIT | Remove light sealers | | |
| 9508-30SB | 30 GRIT | Remove various coatings, and profiles on HARD concrete only | | |
| HALF BAR DIAMOND INSERTS | | | | |
| 9507-6 | 3 GRIT | Remove thin epoxy, paint, adhesives, and sealers | | |
| 9507-12 | 12 GRIT | Remove thin epoxy, paint, adhesives, and sealers | | |
| 9507-16 | 16 GRIT | Remove thin epoxy, paint, adhesives, and sealers | | |
| 9507-16HB | 16 GRIT | Remove various coatings, and profiles on SOFT concrete only | | |
| 9507-30 | 30 GRIT | Removes sealers and preps concrete for polishing | | |
| 9507-30HB | 30 GRIT | Remove various coatings, and profiles on SOFT concrete only | | |
| PROFILING DIAMOND INSERTS | | | | |
| 9510-30 | 30 GRIT | Prep high-/moderate-density concrete for reapplication | | |
| 9510-50 | 50 GRIT | Prep concrete for polishing | | |
| 9510-120 | 120 GRIT | Prep concrete for polishing | | |
| SUPER SOFT, SINGLE BAR DIAMOND INSERTS | | | | |
| 9504-25 | 25 GRIT | Extremely aggressive coating removal with supersoft matrix for hard concrete or heavy cure and seal treatments, perfect for breaking surface tension | | |



9510-120

BRAZED TRAPEZOID DIAMONDS

Used primarily in light industrial and residential applications for concrete grinding and profiling as well as sealer and top coat removal. Provide excellent surface profiles for new coatings, epoxies, or stains. Also create exceptional profiles prior to polishing concrete.

| Description | Best Uses |
|-------------|---|
| 16 GRIT | Remove paint, stain, and sealers; prep concrete for reapplication |
| 30 GRIT | Prep concrete for reapplication and polishing |
| 50 GRIT | Prep concrete for reapplication and polishing |
| 100 GRIT | Prep concrete for polishing |
| | 16 GRIT 30 GRIT 50 GRIT |



9504-25

5-INCH BRAZED DIAMONDS

| Part # | Description | Best Uses |
|----------|-------------|--|
| 9235-16 | 16 GRIT | Remove thin epoxy, paint, stain, adhesives, and heavy sealers |
| 9235-30 | 30 GRIT | Remove adhesives, heavy and light sealers |
| 9235-50 | 50 GRIT | Create a "broom finish" on soft concrete surfaces; first stage to polishing concrete |
| 9235-100 | 100 GRIT | Create a "broom finish" on soft concrete surfaces; first stage to polishing concrete |



5-INCH POLISHING PADS

Used for polishing concrete to various finishes and shines. Resin bond. Available in escalating grits. These polishing pads are for use with all National planetary grinders

| Part # | Description | Best Uses |
|-----------|-------------|---|
| 9267-50 | 50 GRIT | Achieve a "no reflection" polished concrete |
| 9267-100 | 100 GRIT | Follow 9267-50 to create a "little reflection" polished concrete |
| 9267-200 | 200 GRIT | Follow 9267-100 to create a "moderate reflection" polished concrete |
| 9267-400 | 400 GRIT | Follow 9267-200 to create a "satin reflection" polished concrete |
| 9267-800 | 800 GRIT | Follow 9267-400 to create a "shine" polished concrete |
| 9267-1500 | 1500 GRIT | Follow 9267-800 to create a "high shine" polished concrete |
| 9267-3000 | 3000 GRIT | Follow 9267-1500 to create a "mirror" polished concrete |















ACCESSORIES

402757 HELIX® GRIND AND SCRAPE PLATE

The deluxe Helix Grind and Scraper Plate is the most versatile prepping plate in the industry. This magnetic tooling system converts from aggressive grinding and scraping to passive planetary for diamond grinding, carbide/PCD scraping, polishing, and sanding. The Morflex couplers allow the plate to follow the contour of the floor

- Fits the Helix
- Rigid plate mount allows for aggressive grinding and scraping
- Passive planetary tooling creates random scratch pattern
- Polishes and sands without leaving swirl marks
- Morflex couplers reduce the shock to the operator and the machine
- Follows the contour of the floor for uniform operation in low spots
- For use with machines large enough to accept a 16-inch plate with a standard 3 1/4-inch hub
- Converts from grinding to scraping to polishing to sanding in seconds
- Includes three satellite plates that are easily attachable/detachable with cotter pins
- ullet Has a sliding latch that makes the mounting/dismounting of the plate quick and easy





Includes:

- 3 satellites
- •1 dust skirt
- Washers
- All screws/washers needed for installation

73250 TOOLING HOLDER MOUNTING SCREW
73214 FLOATING ISOLATOR ASSEMBLY MOUNTING
SCREW

401882 8274-4 MORFLEX COUPLER 73081 HELIX® SAFETY SCREW 73097 8274-4 SAFETY SCREW 403978: HELIX CLUTCH PLATE